

VIVANCO



STRUJNE LETVE I DODACI

Serije proizvoda i pregled tehnologija

- Vivanco strujne letve dolaze u 4 serije:
 - Standard
 - Basic
 - Comfort
 - Professional
- (Njemački) SCHUKO utikač (CEE 7/3, Type F):
 - Standard utičnica/utikač u većini zemalja Europe. (Izuzetak Francuska, Italija, Danska, Švicarska, Velika Britanija)
 - Ugrađen pol za uzemljenje
- EURO utikač:
 - Manjih dimenzija zbog izuzetka pola za uzemljenje
 - Polovi su fleksibilni radi lakšeg umetanja
- Prenaponska zaštita:
 - Sigurnosna mjera koja štiti uređaje od strujnog udara
 - Najčešći uzročnik strujnog udara su munje

STANDARD



28254

E3 W15-N

- Triple socket extension lead, 1.4 m
- 3 x Schuko
 - Core thickness 1.5 mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing



34433

E3 S15-N

- Triple socket extension lead, 1.4 m
- 3 x Schuko
 - Core thickness 1.5 mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing



28256

ES3 W15

- Triple socket extension lead with switch, 1.4 m lead
- 3 x Schuko with switch
 - Core thickness 1.5 mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing



28257

ES3 S15

- Triple socket extension lead with switch, 1.4 m lead.
- 3 x Schuko with switch
 - Core thickness 1.5 mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing

STANDARD



28258



28259



28260



28261



37323

E6 W15

- Six socket extension lead, 1.4 m lead.
- 6 x Schuko - Core thickness 1.5 mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing

E6 S15

- Six socket extension lead, 1.4 m lead.
- 6 x Schuko - Core thickness 1.5 mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing

ES6 W15

- Six socket extension lead with switch, 1.4 m lead.
- 6 x Schuko with switch - Core thickness 1.5 mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing

ES6 S15

- Six socket extension lead with switch, 1.4 m lead.
- 6 x Schuko with switch - Core thickness 1.5 mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing

ES7 W15

- 7-way Power Socket, switchable, with Shutter, 1.4m.
- max. 3.680W, 16A, 230V~, 50Hz
- 3 Schuko and 4 Euro sockets
- Shutter
- with 2pol switch for switching on/off
- cable length: 1,40m
- cable typ: H05VV-F 3G1.5mm²



27013

EBL 3W

- Triple socket extension lead 1.4 m.
- 3x Schuko - Core thickness 1.5mm²
 - Sockets angled at 45°
 - Virtually unbreakable housing
 - Shutter



61152

EBL 3W 5

- Triple socket extension lead with switch 5 m.
- 3 x Schuko with switch
 - Core thickness: 1.5mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing
 - Shutter



61153

EBL 3B 5

- Triple socket extension lead with switch 5 m.
- 3 x Schuko with switch
 - Core thickness: 1.5mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing
 - Shutter



27014

EBLS 3W

- Triple socket extension lead with switch 1.4 m.
- 3 x Schuko with switch
 - Core thickness: 1.5mm²
 - Sockets angled at 45°
 - Secure contacts
 - Virtually unbreakable housing
 - Shutter

BASIC



27015

EBLS 3S

Triple socket extension lead with switch 1.4 m.

- 3 x Schuko with switch
- Core thickness: 1.5mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing
- Shutter



31044

ELBS 3W3

Triple socket extension lead with switch 3 m.

- 3 x Schuko with switch
- Core thickness: 1.5mm²
- Sockets angled at 45°
- Secure contacts
- Virtually unbreakable housing
- Shutter



27016

EBLS 5W

Five socket extension lead with switch 1.4 m.

- Five socket extension lead with switch
- 5x Schuko with switch
- Core thickness 1.5mm²
- Sockets angled at 45°
- Virtually unbreakable housing
- Shutter



27017

EBLS 5S

Five socket extension lead with switch 1.4 m.

- Five socket extension lead with switch
- 5x Schuko with switch
- Core thickness 1.5mm²
- Sockets angled at 45°
- Virtually unbreakable housing
- Shutter

BASIC



31045

EBLS 5W3

- Five socket extension lead with switch 3 m.
- Five socket extension lead with switch
- 5x Schuko with switch
- Core thickness 1.5mm²
- Sockets angled at 45°
- Virtually unbreakable housing - Shutter



27018

EBLS 6W

- Six socket extension lead with switch 1.4 m.
- Six socket extension lead with switch
- 6x Schuko with switch
- Core thickness 1.5mm²
- Sockets angled at 45°
- Virtually unbreakable housing
- Shutter



27019

EBLS 6S

- Six socket extension lead with switch 1.4 m.
- Six socket extension lead with switch
- 6x Schuko with switch
- Core thickness 1.5mm²
- Sockets angled at 45°
- Virtually unbreakable housing
- Shutter



62328

EBLS 4/4

- 8-Way Multi Socket
- 4 x Schuko sockets, 4x Euro sockets
- core thickness 1.5 mm²
- max.: 3680W/16A
- sockets rotated by 45
- break-proof, high-quality plastic housing
- shutter

BASIC



39613

EBLS 3W2USB

- 3-way power socket with switch, 2x USB, 2.1A max, white 1.4m
- 2x USB socket, max. Output: 5V, 2.1A (total)
- core thickness 1.5 mm²
- sockets turned 45 °
- shatterproof, high quality plastic housing
- Shutter
- max. 3.680W, 16A, 230VAC / 50Hz



61159

EBLS 6SS W

- 6-way power socket with switch and overvoltage protection, white 1.4m
- max. 13.500A leakage current
- core thickness 1.5 mm²
- sockets turned 45 °
- shatterproof, high quality plastic housing
- Shutter
- max. 3.680W, 16A



37654

A 1W2USB

- 6-way power socket with switch and overvoltage protection, black 1.4m
- max. 13.500A leakage current
- core thickness 1.5 mm²
- sockets turned 45 °
- shatterproof, high quality plastic housing
- Shutter
- max. 3.680W, 16A

COMFORT



37643



37644



37645



61171



37646

EKLS 4W

EKLS 4S

EKLS 4W25

EKLS 4B25

EKLS 4W40

- | | | | | |
|--|--|--|--|--|
| COMFORT 4way power socket with switch 1.4 m. | COMFORT 4way power socket with switch 1.4 m. | COMFORT 4way power socket with switch 2.5 m. | COMFORT 4way power socket with switch 2.5 m. | COMFORT 4way power socket with switch 4 m. |
| - 4way power socket with switch | - 4way power socket with switch | - 4way power socket with switch | - 4way power socket with switch | - 4way power socket with switch |
| - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch |
| - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing |
| - Shutter | - Shutter | - Shutter | - Shutter | - Shutter |
| - Wall-mountable | - Wall-mountable | - Wall-mountable | - Wall-mountable | - Wall-mountable |
| - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz |

COMFORT



37647

EKLS 6W



37648

EKLS 6S



37649

EKLS 6W25



37650

EKLS 6W40



37651

EKLS 8W

- | | | | | |
|--|--|--|--|--|
| COMFORT 6way power socket with switch 1.4 m. | COMFORT 6way power socket with switch 1.4 m. | COMFORT 6way power socket with switch 2.5 m. | COMFORT 6way power socket with switch 4 m. | COMFORT 8way power socket with switch 1.4 m. |
| - 6way power socket with switch | - 6way power socket with switch | - 6way power socket with switch | - 6way power socket with switch | - 8way power socket with switch |
| - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch | - Extra large round on-off switch |
| - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing | - Rugged, unbreakable plastic housing |
| - Shutter | - Shutter | - Shutter | - Shutter | - Shutter |
| - Wall-mountable | - Wall-mountable | - Wall-mountable | - Wall-mountable | - Wall-mountable |
| - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz | - 16A / 3.680W / 50Hz |

COMFORT



37326

EKLS 6SS

- 6way Surge protection multi socket, switchable
- 6x Schuko, each socket separate switchable
- 1 ON / OFF main switch
- With surge protection
- Discharge current: 9.000A
- Shutter
- Cable length: 1.8m
- 16A / 3.680W / 50Hz



39612

PC 4W2USB

- 4-way power cube with 2x USB ports, 2.1A max., white 1.4m
- output USB: max. 5V, 2.1A (total)
- core thickness 1.5 mm²
- incl. holder for e.g. wall mounting
- stable contacts, shatterproof, high quality plastic housing
- Shutter
- max. 3.680W, 16A
- 230VAC / 50Hz



62330

EBLS 5W2USBF

- 5-Way Multi Socket, flexible, with switch, white 1.4m
- 5 x Schuko sockets
- core thickness 1.5 mm²
- max.: 3680W/16A
- 2x USB socket, max output: 5V, 2.1A (total)
- flexible positioning
- Shutter
- with switch

PRODUŽNI KABLOVI



22129

EV3W weiß

- Euro extension lead 3 m.
- Euro plug to Euro socket
- Shutter
- Max. 2.5A / 250V~
- Core thickness: 0.75 mm²



22130

EV3S schwarz

- Euro extension lead 3 m.
- Euro plug to Euro socket
- Shutter
- Max. 2.5A / 250V~
- Core thickness: 0.75 mm²



22131

EV5W weiß

- Euro extension lead 5 m.
- Euro plug to Euro socket
- Shutter
- Max. 2.5A / 250V~
- Core thickness: 0.75 mm²



22132

EV5S schwarz

- Euro extension lead 5 m.
- Euro plug to Euro socket
- Shutter
- Max. 2.5A / 250V~
- Core thickness: 0.75 mm²

PRODUŽNI KABLOVI



7278

SKV 2 W

- Schuko Extension 2 m.
- Schuko plug <-> Schuko coupling
- core thickness 1.5 mm²
- max.: 3680W/16A
- 90° angled plug
- Shutter



7280

SKV 3 W

- Schuko Extension 3 m.
- Schuko plug <-> Schuko coupling
- core thickness 1.5 mm²
- max.: 3680W/16A
- 90° angled plug
- Shutter



37324

SKV 3B-N

- Schuko Extension 3 m.
- Schuko plug <-> Schuko coupling
- core thickness 1.5 mm²
- max.: 3680W/16A
- 90° angled plug
- Shutter



7282

SKV 5 W

- Schuko Extension 5 m.
- Schuko plug <-> Schuko coupling
- core thickness 1.5 mm²
- max.: 3680W/16A
- 90° angled plug
- Shutter

PRODUŽNI KABLOVI



37325

SKV 5B-N

Schuko Extension 5 m.
Schuko plug <-> Schuko coupling
core thickness 1.5 mm²
max.: 3680W/16A
90° angled plug
Shutter



7284

SKV 10 W

Schuko Extension 10 m.
Schuko plug <-> Schuko coupling
core thickness 1.5 mm²
max.: 3680W/16A
90° angled plug
Shutter



61157

SKV 10 B

Schuko Extension 10 m
Schuko plug <-> Schuko coupling
core thickness 1.5 mm²
max.: 3680W/16A
90° angled plug
Shutter



61158

SKV 10 O

Schuko Extension 10 m.
Schuko plug <-> Schuko coupling
core thickness 1.5 mm²
max.: 3680W/16A
90° angled plug
Shutter

PRODUŽNÍ KABLOVI



61150

CR 100B

cable reel, indoor 4x Schuko , 10 m

- with thermal fuse to protect against overheating
- max. 3.000W, 16A, 230V
- core thickness 1.5 mm²
- stable contacts, shatterproof, high quality plastic housing
- Shutter



39614

CR 75B

cable reel, indoor 4x Schuko , 7.5 m

- with thermal fuse to protect against overheating
- max. 3.000W, 16A, 230V
- core thickness 1.5 mm²
- stable contacts, shatterproof, high quality plastic housing
- Shutter

PROFESSIONAL



37656

EPLS 4ALU

PROFESSIONAL power socket with switch.

- With surge protection
- With on-off switch
- Robust aluminum housing
- Wall-mountable
- Shutter
- Extra flat plug design, ideal for placement behind cabinets or sideboards
- Cable: 1.6m - Max. 30.000A leakage current
- 16A / 3.680W / 50Hz



37657

EPLS 6ALU

PROFESSIONAL power socket with switch.

- With surge protection
- With on-off switch
- Robust aluminum housing
- Wall-mountable
- Shutter
- Extra flat plug design, ideal for placement behind cabinets or sideboards
- Cable: 1.6m - Max. 30.000A leakage current
- 16A / 3.680W / 50Hz



37658

EPLS 4USB_ALU

PROFESSIONAL 4way power socket + USB charger + overvoltage protection, switchable.

- 4-way power socket
- 2x USB socket, max. 5V, 2.1A
- With surge protection
- With on-off switch
- Robust aluminum housing
- Wall-mountable
- Shutter
- Extra flat plug design, ideal for placement behind cabinets or sideboards
- Schuko plug with special pull out ring
- Cable: 1.6m
- Max. 30.000A leakage current
- 16A / 3.680W / 50Hz

PROFESSIONAL



37659

EPLS 3_1ALU2M

- PROFESSIONAL power socket with switch.
- Power socket with switch
 - Extra slot for large power supplies
 - With surge protection
 - With on-off switch
 - Robust aluminum housing
 - Wall-mountable
 - Shutter
 - Extra flat plug design, ideal for placement behind cabinets or sideboards
 - Cable: 2.0m - Max. 30.000A leakage current
 - 16A / 3.680W / 50Hz



37660

EPLS 5_1ALU2M

- PROFESSIONAL power socket with switch.
- Power socket with switch
 - Extra slot for large power supplies
 - With surge protection
 - With on-off switch
 - Robust aluminum housing
 - Wall-mountable
 - Shutter
 - Extra flat plug design, ideal for placement behind cabinets or sideboards
 - Cable: 2.0m - Max. 30.000A leakage current
 - 16A / 3.680W / 50Hz



37661

EPLS 7_1ALU2M

- PROFESSIONAL power socket with switch.
- Power socket with switch
 - Extra slot for large power supplies
 - With surge protection
 - With on-off switch
 - Robust aluminum housing
 - Wall-mountable
 - Shutter
 - Extra flat plug design, ideal for placement behind cabinets or sideboards
 - Cable: 2.0m
 - Max. 30.000A leakage current
 - 16A / 3.680W / 50Hz



34430

EP 5SO

- 5way Professional Line power socket with surge and overload protection.
- 5way Professional Line power socket
 - With surge protection, type 3, max. discharge current of 13.500A
 - With overload protection with RESET function
 - Shutter
 - Switchable
 - Cable length: 1.40m
 - Cable type: H05VV-F 3G1.5mm²
 - Max. 16A, 3.680W
 - CE / GS approved

ADAPTERI



7295

A2 W

2-way Euro adapter, white
- Schuko plug to 2 x Euro socket



31047

A3 WE

3way Euro Adapter.
- Shutter
- Max. 1.700W



17462

A3 W

Schuko-/Euro Adapter.
- Schuko plug to 1 x schuko socket and 2 x euro socket
- Shutter

ADAPTERI



22396



27369



21950



34422

AS 1W

AS 3W

ÜSP 1W

A 1W2USB

Schuko adapter with switch.
- Schuko plug to Schuko socket with switch
- Shutter

Schuko adapter with switch
- 1x Schuko plug <-> 1x Schuko socket & 2x Euro socket
- Shutter
- Virtually unbreakable housing

Overvoltage protection adapter, white
- For protecting your electrical devices from overvoltage, e.g. from lightning
- Including function LEDs - Shutter
- Max. connection power: 16 A / 3500 W
- Leakage current 2 x 4500 A

power adapter with 2x USB, 2.1A max
- Schuko plug <-> 1x Schuko coupling and 2x USB socket
- output USB: max. 5V, 2.1A (total)
- Shutter
- maximum load capacity: 16A / 3.680W
230VAC / 50Hz

PUTNI ADAPTERI



7292



36217



36218



39615

RS 4 W

TAS EUROPE

TAS WORLD

TA WORLD/EU

Travel plug set
- Southern Europe
- America
- Overseas
- UK

Travel Adapter Set Europe. For connecting devices with Schuko and Euro plug to electrical outlets abroad with different socket systems. Caution: The travel plug is not a voltage or frequency converter! Ideal for travel in Europe, includes connectors for:
- United Kingdom
- Switzerland
- Italy

Travel Adapter Set World. For connecting devices with Schuko and Euro plug to electrical outlets abroad with different socket systems. Caution: The travel plug is not a voltage or frequency converter! Ideal for World Travel, includes connectors for:
- United Kingdom
- USA
- Australia + China

Travel Adapter World - Europe white
This Adapter adapts the following plug types: Plug type A, B (USA), max. load: 125V~, 15A, 1.800W, Plug type G (GB), max. load: 250V~, 10A, 2.300W (230V), Plug type I (AUS/CN), max. load: 250V~, 10A, 2.300W (230V), Plug type J (CH), max. load: 250V~, 10A, 2.300W (230V), Plug type L (IT), max. load: 250V~, 10A, 2.300W (230V) to Plug type E+F (EU), max. load: 250V~, 10A, 2.300W (230V)

PUTNI ADAPTERI



28692

TA AUS/D

Travel Adapter for Australia / China
 - Adapts one AUS / CN plug to a schuko socket
 - Max. load: 250V~, 10A, 50Hz
 - Small and space saving housing
 - Attention: The travel adapter is not a voltage or frequency converter!



28693

TA GB/D

Travel Adapter for Great Britain
 - Adapts one GB plug to a schuko socket
 - Incl. shutter
 - Max. load: 250V~, 13A, 50Hz
 - Small and space saving housing Attention:
 The travel adapter is not a voltage or frequency converter!



28699

TA D/GB

Travel Adapter for Great Britain
 - adapts one schuko plug to a GB socket
 - Shutter and 13A fuse
 - Max. load: 250V~, 13A, 50Hz
 - Small and space saving housing
 - Attention: The travel adapter is not a voltage or frequency converter!



28695

TA CH/D

Travel adapter Switzerland, swiss socket - schuko plug.
 - Adapts one swiss plug to a schuko socket
 - Shutter
 - Max. load: 250V~, 10A, 50Hz
 - Small and space saving housing
 - Attention: The travel adapter is not a voltage or frequency converter!

PUTNI ADAPTERI



33504



28694



34436



28700

TA D/CH

TA D/USA

TA USA/D-N

TA I/D

Travel adapter Swiss, schuko socket - swiss plug.

- Adapts one schuko plug to a swiss socket
- Shutter - Inkl. 10A fuse
- Max. load: 250V~, 10A, 50Hz
- Attention: The travel adapter is not a voltage or frequency converter!

Travel adapter USA, schuko socket - USA 3pin plug.

- Travel Adapter for USA
- Adapts one schuko plug to an USA socket
- Shutter
- Max. load: 250V~, 15A, 50Hz
- Small and space saving housing
- Attention: The travel adapter is not a voltage or frequency converter!

Travel adapter USA, USA socket - schuko plug.

- Travel Adapter for USA
- Adapts one USA plug to a schuko socket
- Max. load: 250V~, 15A, 50Hz
- Small and space saving housing
- Attention: The travel adapter is not a voltage or frequency converter!

Travel adapter Italy, italian socket - schuko plug.

- Adapts one italian plug to a schuko socket
- Shutter
- Max. load: 250V~, 16A, 50Hz
- Small and space saving housing Attention: The travel adapter is not a voltage or frequency converter!



39618

CO M10Y

CO alarm, to protect against toxic carbon monoxide

- with integrated 7 years lifetime sensor
- recommended by chimney sweeper
- alarm signal: 85 dB <1m>
- with function LED
- dimensions: mm 120 x 80
- batteries, screws + dowels included

potential cause of risk are: chimney, gas stove, gas heating system, oil-, wood burning- and cockle stove



33510

SD 3-N

Smoke Detector

- Tested according to smoke detector standard EN14604
- CE certified - Incl. 9V battery
- With function LED and audible signal
- With self test function
- Automatic function control
- With alarm function when the battery power isn't high enough
- Easy and wireless installation
- Incl. instruction manual in 17 languages



36215

SD 3-N SET

Smoke Detector Set

- Tested according to smoke detector standard EN14604
- CE certified - Incl. 9V battery
- With function LED and audible signal
- With self test function
- Automatic function control
- With alarm function when the battery power isn't high enough
- Easy and wireless installation
- Incl. instruction manual in 17 languages
- Contains 4 pcs



33509

SD 10Y

10 years smoke alarm

- 10 years smoke alarm
- With built in Lithium Longlife Battery
- With function LED and Hush function
- Includes alarm memory
- Tested and certified according to EN14604
- Installation material included
- Installation sheet included



34426

MH SD1

Magnetic holder for smoke detector

- Quick and clean assembling
- Fits for almost all smoke detectors
- Also suitable for CO alarm, heat alarm and other, similar devices
- 3M glue tape for a safe and permanent assembling
- Incl. instruction manual

UTIČNICE NA DALJINSKO UPRAVLJANJE



62353

FSS3680 W

- 5-Way Multi Socket, flexible, with switch
- 2x Schuko socket receiver with switch
- 2-way RF power socket set with auto-learn function for easy pairing
- 3.680W maximum load capacity per socket adapter
- Convenient switching of devices up to 25 m range
- Stand by power consumption: <1W
- Incl. manual and battery



34434

FSS 31000W

- 3way RF power socket set with auto learn function
- Set contains 1 wireless remote control and 3 wireless power outlet receivers
- With auto learn function for easy pairing
- Switching capacity: max. 1000W per receiver
- Coverage: up to 25 m
- Power consumption: > 1W
- Incl. battery and instruction manual

OUTDOOR



37671

FSS 21000B IP44

- 2-way RF power socket set, black
- with auto-learn function for easy pairing
- 1000W maximum load capacity per socket adapter
- IP44 certified
- convenient switching of devices up to 25 m range



37672

T24 IP44

- Mechanical timer for outdoor use
- IP44 certified
- Maximum 48 switching options per day
- Shortest switching distance: 30 minutes
- Integrated Shutter
- Voltage: 220-240V / 50Hz
- Max. Load: 16A / 3600W
- Operating temperature: 10 to 40 ° C



39610

AS 1B IP44

- Outdoor power adapter
- protection against splash water and sand
- Schuko plug <-> Schuko socket
- IP44 certified
- integrated Shutter
- voltage: 220-240V / 50Hz
- max. Load: 16A / 3680W
- operating temperature: -10 to 40 ° C



39607

ES3 B20 IP44

- 3way power socket with switch, 2m, black
- IP44 certified
- Core cross section: 1.5mm², cable type: H07RN-F3G 1.5mm²
- Sockets angled at 45°
- High quality, unbreakable housing
- With Shutter

OUTDOOR



39609

E4 B14 IP44

- Outdoor power adapter 4-way, 1.4m
- protection against splash water and sand.
- IP44 certified
- core cross section: 1.5mm², cable type: H07RN-F3G 1.5mm²
- slots rotated 45 °
- voltage: 220-240V / 50Hz
- max. Load: 16A / 3680W
- operating temperature: -10 to 40 ° C



61155

GS2 H07RN

- Outdoor 2-way power socket with earth spike
- 2 protective contact sockets with self-closing cover
- Robust, weatherproof plastic housing
- Splashproof, IP 44
- Supply cable: 3m (H07RN-F 3G1.5 mm²)
- 230 V~; 16 A; 50 Hz; max. 3680 W
- Fixed rubber supply line with earthing contact plug



61147

SKV 05RR 10B

- Outdoor extension cable 10m, black
- cable type H05RR-F
- IP44 certified
- with children safety
- with protective cap
- max 3,200W, 16A, 230V



61148

SKV 05RR 25B

- Outdoor extension cable 25m, black
- cable type H05RR-F
- IP44 certified
- with children safety
- with protective cap
- max 3,200W, 16A, 230V



61149

SKV 05RR 25R

- Outdoor extension cable 25m, red
- cable type H05RR-F
- IP44 certified
- with children safety
- with protective cap
- max 3,200W, 16A, 230V

OUTDOOR



61154

SKV3 07RN 10B

- Outdoor extension cable 10m, black
- cable type H07RN-F
 - IP44 certified
 - with children safety
 - with protective cap
 - max 3,200W, 16A, 230V



61151

CR 07RN IP44 40

- Cable reel outdoor metal, 40m
- 4 x Schuko slot, wire thickness 1.5 mm²
 - cable type H07RN, IP44 certified
 - with protective caps, stable metal frame
 - robust carrying handle, rotating handle for easy rolling up with thermal fuse to protect against overheating
 - Max. 3,200W, 16A, 230V
 - with children safety



61145

CR 05VV IP44 25

- Cable reel outdoor, 25m
- 4 x Schuko slot, wire thickness 1.5 mm²
 - cable type H05VV, IP44 certified
 - with protective caps, stable frame
 - robust carrying handle, rotating handle for easy rolling up with thermal fuse to protect against overheating
 - Max. 3,200W, 16A, 230V
 - with children safety



61146

CR 05VV IP44 50

- Cable reel outdoor, 25m
- 4 x Schuko slot, wire thickness 1.5 mm²
 - cable type H05VV, IP44 certified
 - with protective caps, stable frame
 - robust carrying handle, rotating handle for easy rolling up with thermal fuse to protect against overheating
 - Max. 3,200W, 16A, 230V
 - with children safety